

0.5 SQ. FEET SCREEN AREA

160 °F DESIGN TEMPERATURE 150 PSI DESIGN PRESSURE ~120 LBS. EMPTY WEIGHT ~200 LBS. FULL WEIGHT

NOTES: 1. PLEASE ALLOW \sim 5" ADDITIONAL TO INSTALL AND REMOVE THE PISTON ASSEMBLY TO THE BACKSIDE OF THE FILTER.

UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED. DRAWING, DESIGN AND OTHER DISCLOSURES PROPERTY OF TEKLEEN AUTOMATIC FILTERS, INC.

NOZZLE	CONNECTION	TYPE	SIZE	RATING	TOLERANCES (UNLESS OTHERWISE SPECIFIED)	TEKLEEN
K1	HIGH PRESSURE CONN.	THREADED	1/4" NPT(2)		(,	Automatic Fliters inc.
K2	LOW PRESSURE CONN.	THREADED	1/4" NPT		FRAC. ±1/16 ANGLE ±1° .X ±.1 .XX ±.05 .XXX ±.010	2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 MAIN: (310) 839-2828
K3	HYDRAULIC CONN.	THREADED	1/4" NPT			FAX: (310) 839-6878
N1	INLET	THREADED	2" NPT		MATERIAL: SST	TITLE: LPF2—LP FILTER, CUT DRAWING,
N2	OUTLET	THREADED	2" NPT		DRAWN BY: S. PERKINSON	2" FLUSH VALVE
					DATE: 12/09/2016	DRAWING NUMBER REV
N3	FLUSH OUTLET	THREADED	2" NPT		SCALE: 1:7 SHEET: 1 OF 1	LPF-2LP-CUT-01 N/A