



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**TECHNICAL DATA**

Flow Rate	Max. 20,000 GPM
Screen Size	---- Micron
Screen Area	48.0 sq.ft (Perf.)
Working Temp.	200 deg. F
Working Pressure	150 PSI
Empty Weight	---- lbs.
Full Weight	---- lbs.

NOZZLE	CONNECTION	TYPE OF CONNECTION	SIZE	RATING
K1	Hi. Press. Conn.	Threaded	1/4" NPT(2)	150 lbs. F.F. 150 lbs. F.F.
K2	Low Press. Conn.	Threaded	1/4" NPT (2)	
K3	Hydraulic Conn.	Threaded	1/4" NPT(2)	
N1	Inlet	Flanged	24" ASA	
N2	Outlet	Flanged	24" ASA	
N3	Flushoutlet	Threaded	2" NPT	

<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES</small> DECIMALS    ANGULAR XX ± .05    ± 0.5 DEG XXX ± .01		<b>AUTOMATIC FILTERS, INC.</b> 2672 S. LA CIENEGA BLVD. LOS ANGELES, CA 90034 (310) 839-2828 FAX (310) 839-6878	
DRAWN Daniel Stenberg		DATE 2-27-06	
CHECKED		TITLE <b>CSB 24-TS Coarse Screen Brush Filter</b>	
DESIGN	SIZE A	DWG NO. <b>CSB24-TS</b>	REV 0
NOT TO SCALE		SHEET OF	